

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/102004 A1

(51) International Patent Classification⁷: F04C 29/00,
29/06, 15/00

(21) International Application Number:
PCT/KR2004/000999

(22) International Filing Date: 30 April 2004 (30.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2003-0030342 13 May 2003 (13.05.2003) KR

(71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, Seoul 150-721 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BAE, Ji Young [KR/KR]; Yongho 2- dong, 521-18, Nam-gu, Busan 608-767 (KR). ROH, Chul Gi [KR/KR]; Daedong


APT., 123-2204, Sangnam-dong, 44-1, Changwon-si, Gyeongsangnam-do 631-050 (KR). PARK, Kyoung Jun [KR/KR]; H-210, LG Electronics Dormitory, Gaumjung-dong, Changwon-si, Gyeongsangnam-do 641-711 (KR). JANG, Chang Yong [KR/KR]; Builim APT., 101-1005, Maegok-dong, Buk-gu, Gwangju 500-815 (KR). KIM, Jong Bong [KR/KR]; Hyundai APT., 105-1201, Banlim-dong, 3-1, Changwon-si, Gyeongsangnam-do 641-767 (KR). KO, Young Hwan [KR/KR]; GMB APT., 514, Gaumjung-dong, 12-6, Changwon-si, Gyeongsangnam-do 641-711 (KR).

(74) Agents: BAHNG, Hae Cheol et al.; KIMS INTERNATIONAL PATENT & LAW OFFICE, 15th Floor Yo Sam Building, 648-23, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,

[Continued on next page]

(54) Title: ROTARY COMPRESSOR



(57) Abstract: Disclosed is a rotary compressor having two compression capacities. The rotary compressor includes: a driving shaft (18) being rotatable clockwise and counterclockwise, and having an eccentric portion (13a) of a predetermined size; a cylinder (21) forming a predetermined inner volume; a roller (22) installed rotatably on an outer circumference of the eccentric portion (13a) so as to contact an inner circumference of the cylinder (21), performing a rolling motion along the inner circumference and forming a fluid chamber (29) to suck and compress fluid along with the inner circumference; a vane (23) installed elastically in the cylinder to contact the roller continuously; a first bearing (24) installed in the cylinder (21), for supporting the driving shaft (13) rotatably; a second bearing (25) for rotatably supporting the driving shaft (13) and preliminarily storing the fluid to be sucked; discharge ports (26) communicating with the fluid chamber (29); and a valve assembly (110) having openings separated by predetermined angle from each other, for allowing the openings (111, 112, 113) to selectively communicate with the second bearing (25) at a predetermined position of the fluid chamber (29) according to rotation direction of the driving shaft (18), wherein compression spaces that have different volumes from each other are formed in the fluid chamber (29) according to the rotation direction of the driving shaft (13) so that two different compression capacities are formed.



MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.